

# ABUS






## 83/55

-  11.5 mm
-  25.5 mm
-  25 mm  
38 mm  
50 mm  
75 mm



## 83CS/55

-  11.5 mm
-  25.5 mm
-  28 mm






## 83/60

-  11.5 mm
-  25.5 mm
-  25 mm  
38 mm  
50 mm  
75 mm



## 83/80

-  15 mm
-  40 mm
-  38 mm  
80 mm



## 83/55 & 83CS/55

- Chrome, hardened steel body with
- Nano-Protect plating
- Double shackle ball locking
- Alloy steel shackle with Nano-Protect™ plating for security and excellent corrosion resistance
- Removable core cylinder for quick rekeying
- Patented Z-Bar allows padlock to be easily converted from non key-retaining to key-retaining
- Compatible with most restricted keying systems including Lockwood, Bilock and Kaba
- Accepts most KNK cylinder assemblies
- SCEC approved for SL3 (with an approved keying system & key retained)

## 83/60

- Chrome, hardened steel body with
- Nano-Protect plating
- Double shackle ball locking
- Alloy steel shackle with Nano-Protect™ plating for security and excellent corrosion resistance
- Removable oval cylinder for quick rekeying
- Patented Z-Bar allows padlock to be easily converted from non key-retaining to key-retaining
- Compatible with most restricted keying systems including Lockwood, Bilock and Kaba
- SCEC approved for SL3 (with an approved keying system & key retained)

## 83/80

- Chrome, hardened steel body with
- Nano-Protect plating
- Triple shackle ball locking
- Alloy steel shackle with Nano-Protect™ plating for security and excellent corrosion resistance
- Removable oval cylinder for quick rekeying
- Patented Z-Bar allows padlock to be easily converted from non key-retaining to key-retaining
- Compatible with most restricted keying systems including Lockwood, Bilock and Kaba
- SCEC approved for SL4 (with an approved keying system & key retained)